



REY CERA CREATION PVT. LTD.

(CIN No. U26933GJ2015PTC083940)

8-A, National Highway, Sartanpar Road, Opp. Kevin Ceramic,
At. Ratavirda, Tal. Wankaner, Dist. Morbi - 363 621 (INDIA),
info@reycera.com www.reycera.com +919099906544



DECLARATION OF PERFORMANCE REPORT

Declaration of Performance Report No: REY/DOP/ROM/EXP/A2902/24-25

1. Identification of Product : Dry pressed ceramic wall tiles, $E_b \geq 3\%$
2. Intended Use(s) : For internal wall use
3. Name and contact address of manufacturer:
REY CERA CREATION PVT. LTD., 8-A, NATIONAL HIGHWAY, SARTANPAR ROAD, AT.RATAVIRDA,
DIST. MORBI 363621 (GUJARAT) INDIA
4. System or systems of assessment and verification of constancy of performance of the construction product : System 4

According to the Regulation (EU) No.: 305/2011 of the European Parliament and of The Council the product group which reference number is given above confirm all the requirements of EN 14411:2012 standard for ceramic tiles.

5. Detailed Performance Declared as under :

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	A 1 fl	EN 14411:2012
Resistance to fire	Fireproof	
External fire performance	Pass	
Noise absorption	Pass	
Emissions of dangerous substances	Pass	
Release of dangerous substance, for -Cadmium	Pass	EN 14411:2012
-Lead		
Breaking Strength	Thickness ≥ 6.5 mm. min. S:700 N Thickness < 6.5 mm. min. s:500 N	
Slipperiness	Anti-slip products are defined on the package	
Tactility	Pass	
Bond Strength/adhesion for:		
Cementations adhesive, type C2	Min, 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
-Internal use:	Pass	
-external use: freeze-thaw resistance	notpass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on half of the manufacturer by:

GENERAL MANAGER
Mr. Mohammad Nazir
29.05.2024

